

Author
Nam Paik
 Director of
 Engineering
 TSi Power

The Merits Of A Standby UPS With A Modified Sinewave Output



Of the 3 major UPS architectures (e.g. Standby, Ferroresonant On-Line, and Double-Conversion On-Line), the Standby UPS features the following advantages:

	Features	Benefits
1.	Extremely high power efficiency, typically above 97%.	Lowest operating cost in terms of electric use – only 1/10 of double-conversion on-line UPS.
2.	Air exhaust fan is normally off since very little heat is generated.	Quiet operation. Does not add to air conditioning loads.
3.	The inverter circuit is normally off.	Very quiet operation and the highest MTBF (mean-time-between failure) due to the lowest voltage, current and temperature of its internal parts.
4.	Cooler internal operating temperature.	Battery lifetime is approximately twice that of an on-line type UPS.
5.	Output waveform is normally a sinewave. The inverter waveform is a modified square-wave, generated only during power outages.	The pulse-width-modified and optimized peak-voltage modified square waveform is actually more beneficial for switchmode power supplies.
6.	Simplest and most economical UPS design.	Simple design with the lowest parts count. Means lowest purchase price and maintenance costs. Repair procedures are quick and easy.
7.	The switchover time of some high-quality Standby UPS is less than 1ms.	The ride-through of a typical switchmode power supply is 10 to 20 ms. A fast 1 ms switchover time guarantees glitch-free transfers.



TSi Power Corporation
 1103 West Pierce Avenue
 Antigo, WI 54409
 USA
 715.623.0636
 800.874.3160
 Fax 715.623.2426
 sales@tspower.com
 www.line-conditioner.com

About The Author

Nam Paik ~ Director of Engineering, TSi Power Corporation

Mr. Paik has over 15 years experience in the power electronics industry. He was with Northern Telecom (now Nortel Networks) for 4 years prior to joining TSi Power in 1988. Nam has focused on UPS, Line Conditioner and DC to AC inverter products and most recently has developed a number of customized power protection and conversion systems for several U.S. government agencies and international applications.

Additional Benefits Provided by an Isolation Line Conditioner (or UPS):

1. Regeneration of power using the isolation transformer at the point of use means that it is a truly ideal power source (It is like moving the building transformer to within a few feet of sensitive equipment). The power from an isolation transformer is both DEDICATED and ISOLATED.
2. Multi-stage surge protectors and EMI/RFI noise filters are also built-in.
3. ISOLATION CONDITIONER sizes ranging from 90 VA to 5.5 kVA allows optimized performance vs. cost product selection. UPS size ranges from 400VA to 2,100 VA.
4. Installation is immediate and no permit or approval is required. (Conditioners are also available in sizes up to 36 kVA, and it is recommended they be installed by a licensed electrician).
5. Cost of the unit is only a small fraction of a dedicated circuit installation cost.

About The Author

Nam Paik ~ Director of Engineering, TSi Power Corporation

Mr. Paik has over 15 years experience in the power electronics industry. He was with Northern Telecom (now Nortel Networks) for 4 years prior to joining TSi Power in 1988. Nam has focused on UPS, Line Conditioner and DC to AC inverter products and most recently has developed a number of customized power protection and conversion systems for several U.S. government agencies and international applications.



TSi Power Corporation
1103 West Pierce Avenue
Antigo, WI 54409
USA
715.623.0636
800.874.3160
Fax 715.623.2426
sales@tsipower.com
www.line-conditioner.com

Copyright © 2004 TSi