

Outdoor UPS

Dc output

wide temperature batteries

wide ac input voltage window

Outdoor UPS model

8009

60 watts
input can be
115 or 230 vac
output is
12 vdc
1.3 hrs @60W
2.5 hrs @36W
-20° to +60°C;
-40° to +60°C
with optional
battery heater

8010

60 watts
input can be
115 or 230 vac
output is
12 vdc
5 hours @60W
8 hours @36W
-20° to +60°C;
-40° to +60°C
with optional
battery heater

Outdoor on-line UPS with dc output

The TSi Power Outdoor-UPS-8009/8010 with dc output are for dc powered applications needing backup power in extreme weather conditions. They are constructed with wide temperature batteries and are housed in a weather protected IP44 (NEMA-3R) enclosure. These offer a wide input voltage window (88–264 vac) and low ripple 12 vdc output, with heavy duty surge protection and noise filtering.

Key Outdoor UPS benefits

This rugged outdoor dc output UPS design is suitable for use in severe outdoor environments.

Outdoor UPS extreme/wide temperature batteries allow operation of the UPS system over an ambient temperature range of -20° to +60°C (-4° to +140°F); -40° to +60°C (-40° to +140°F) with optional battery heater.

The wide input voltage window enables dc output without having to drain or exercise the batteries, thereby ensuring long battery life.

Battery run-times for the Outdoor-UPS-8009 are approximately 1.3 hours at 60 watts load, and 2.5 hours at a 36 watts load. For the Outdoor-UPS-8010, approximately 5 hours at 60 watts load, and 8 hours with a 36 watts load.

How the Outdoor UPS works

The outdoor UPS with dc output provides extended battery backup through a system which takes nominal 115 or 230 vac input (from 88–264 vac), converts it to dc, charges the batteries, and delivers a nominal 12 vdc (10–14 vdc) with a less than 200 millivolts peak to peak ripple. The heavy duty surge protection and noise filtering on the ac input helps protect the unit and load from transient surges on the line.

Because the unit is already delivering dc power, upon a deep brownout or loss of power, the Outdoor UPS with dc output has a zero transfer time to the reserve power in the batteries.

For OEMs, a small 'hotel' space is provided inside the unit for your equipment to reside.



Typical applications

These heavy duty outdoor UPS systems are designed to power wireless communications, perimeter surveillance cameras (CCTV), security/gate control systems, LED traffic light/roadway display systems and industrial remote terminal units (RTUs).

Key Outdoor UPS features

- Cabinet can be pedestal (ground), pole, or wall mounted
- Full weather outdoor protection IP44 (NEMA-3R) metal cabinet
- Dc output with low ripple
- Wide temperature batteries
- Heavy-duty surge protection and noise filtering
- Wide ac input voltage window lengthens battery life
- Two year warranty on electronics
One year warranty on batteries



TSi Power Corporation
1103 West Pierce Ave
Antigo, WI 54409 USA
800 874 3160 (USA only)
Phone +1 715 623 0636
Fax +1 715 623 2426
sales@tsipower.com
www.tsipower.com
Copyright © 2008 TSi

Outdoor UPS



Outdoor dc output UPS with a wide ac input voltage window and extreme/wide temperature batteries

Specification	Outdoor-UPS-8009	Outdoor-UPS-8010
Electrical		
Capacity in watts	60 watts	
UPS topology	Ac to dc rectifier, battery charger and sealed gel-cell batteries	
Input		
Nominal voltage	115 or 230 volts ac	
Operating voltage	88–264 vac without using batteries	
Input current	1 A maximum @ 115 vac, or 0.5A maximum @ 230 vac	
Operating frequency	50 or 60Hz (47–63Hz)	
Output		
Nominal voltage	12 volts dc	
Operating voltage	10–14 volts dc (depending on battery charge status)	
Output current	5 amperes maximum @ 12 vdc	
Dc ripple voltage	Less than 200 millivolts peak to peak	
Power efficiency	84% (typical)	
Power on/off switch	On/off rocker style power switch	
Transfer time to backup	Zero transfer time	
Battery backup time	1.3 hours @ 60 watts (5A) load, 2.5 hours @ 36 watts (2.5A) load.	5 hours @ 60 watts (5A) load, 8 hours @ 36 watts (2.5A) load.
Recharge time	4 hours to 90% capacity after full discharge.	16 hours to 90% capacity after full discharge.
Batteries	10 ampere hours, 12vdc Wide temperature sealed gel-cells -20° to +60°C (-4° to +140°F); -40° to +60°C (-40° to +140°F) with optional battery heater.	30 ampere hours, 12vdc
Ac connections	3 position terminal block provided for 3 x 1 mm ² (18AWG), L1, L2 and Ground connections via 12mm (1/2") diameter liquid-tight cable glands.	
Dc connections	2 position terminal block provided for dc output wires connection via 19mm (3/4") diameter liquid-tight cable glands.	
Physical		
Dimensions	304mm (12") wide x 381 mm (15") high x 152mm (6") deep	
Weights	14kg (30 lbs)	21 kg (45 lbs)
Steel cabinet	Full weather IP44 (NEMA 3R) UL50 outdoor padlockable enclosure.	
Mounting options	Pole mountable to monopole via optional 'H' style bracket (mounting bands not included). Wall mountable via enclosure's top+bottom brackets. Also, optional pedestal (ground) brackets are available.	
'Hotel' space for OEM option	Approximately 254mm (10") wide x 76mm (3") high x 152mm (6") deep, (if more space is needed, unit can be built with a larger enclosure).	
Environmental		
Operating temperature, battery heater option	-20° to +60°C (-4° to +140°F) ambient air temperature. -40° to +60°C (-40° to +140°F) with optional battery heater.	
Warranty		
Warranty	Two year limited warranty, parts and labor. One year battery warranty.	

TSi's ongoing product improvement process makes specifications subject to change. Other companies product names herein are for identification purposes only, and may be trademarks of their respective companies.



TSi Power Corporation
1103 West Pierce Ave
Antigo, WI 54409 USA
800 874 3160 (USA only)
Phone +1 715 623 0636
Fax +1 715 623 2426
sales@tsipower.com
www.tsipower.com
Copyright © 2008 TSi



Outdoor UPS



optional bandable or boltable monopole mounting brackets



Outdoor-UPS-8009/8010 at a glance

Heavy-duty outdoor on-line UPS with dc output, wide ac input voltage window, and wide temperature batteries

- Wide ambient temperature range sealed gel-cell batteries: -20° to +60°C (-4° to +140°F); or -40° to +60°C (-40° to +140°F) with optional thermostat controlled battery heater
- Low dc output ripple
- 12 vdc battery bus
- **1.3 hours @ 60 watts load**, or 2.5 hours @ 36 watts load with **the Outdoor-UPS-8009**
- **5 hours @ 60 watts load**, or 8 hours @ 36 watts load with **the Outdoor-UPS-8010**
- Nominal 12 volts dc (10–14vdc) output from 88–264 vac input without going to batteries
- Weather protected IP44/NEMA-3R, UL50 painted metal cabinet
- Optional pole, wall or floor mounting brackets available. Must be specified/ordered at time of purchase order.
- Larger OEM 'hotel' space is available, please call if more space is necessary.



TSi Power Corporation
 1103 West Pierce Ave
 Antigo, WI 54409 USA
 800 874 3160 (USA only)
 Phone +1 715 623 0636
 Fax +1 715 623 2426
 sales@tsipower.com
 www.tsipower.com
 Copyright © 2008 TSi



ac input is via a 12 mm (1/2") diameter liquid-tight cable gland, and dc output is via a 19 mm (3/4") diameter liquid-tight cable gland

This page intentionally left blank.



TSi Power Corporation
1103 West Pierce Ave
Antigo, WI 54409 USA
800 874 3160 (USA only)
Phone +1 715 623 0636
Fax +1 715 623 2426
sales@tsipower.com
www.tsipower.com
Copyright © 2008 TSi